

Replicant - Issue #1719

Retrieving the Replicant release key from a key server does not work

06/28/2016 09:54 PM - Fil Lupin

Status:	Closed	Start date:	06/28/2016
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Website and wiki content	Estimated time:	0.00 hour
Target version:	Any version	Spent time:	0.00 hour
Resolution:		Grant:	
Device:		Type of work:	
Description			
To get Launching the command "gpg --recv-key 4A80EB23" (http://redmine.replicant.us/projects/replicant/wiki/ReplicantReleaseKey) does not give any answer. Using web interface neither (http://keys.gnupg.net/).			

History

#1 - 06/29/2016 10:22 AM - Francesco Turco

Works for me.

#2 - 07/16/2016 11:28 PM - Tiberiu T

- File *replicant.pub* added

It works for me too:

```
gpg --recv-key 4A80EB23
gpg: requesting key 4A80EB23 from hkp server keys.gnupg.net
gpg: key 4A80EB23: "Replicant project release key <contact@replicant.us>" not changed
gpg: Total number processed: 1
h3. gpg:                unchanged: 1
```

Fil, you might need to try a command which selects a different key sever:

```
gpg --keyserver pgp.mit.edu --recv-key 4A80EB23
gpg: requesting key 4A80EB23 from hkp server pgp.mit.edu
gpg: key 4A80EB23: "Replicant project release key <contact@replicant.us>" not changed
gpg: Total number processed: 1
gpg:                unchanged: 1
```

Using the web interface of pgp.mit.edu:

<http://pgp.mit.edu/pks/lookup?op=vindex&search=0x16D1FEEE4A80EB23>

you can copy the key in a local file *replicant.pub*:

<http://pgp.mit.edu/pks/lookup?op=get&search=0x16D1FEEE4A80EB23>

and import it in your key ring:

```
gpg --import replicant.pub
gpg: key 4A80EB23: "Replicant project release key <contact@replicant.us>" not changed
gpg: Total number processed: 1
gpg:                unchanged: 1
```

PS To help you, I'm also attaching the *replicant.pub* here, you can compare it with the one from the key server and use it if it's the same.

#3 - 08/03/2016 10:54 PM - Fil Lupin

Tiberiu-Cezar Tehnoetic wrote:

Fil, you might need to try a command which selects a different key sever:

[...]

Using the web interface of pgp.mit.edu:

Thank you, using a specific server (pgp.mit.edu) make it works even if default one bugs.
The public key also is the same, thank you.

#4 - 10/22/2016 09:53 PM - Loic Dachary

- Status changed from New to Closed

Closing since it appears to be a transient error from the server:

```
$ gpg --keyserver keys.gnupg.net --recv-key 4A80EB23
gpg: requesting key 4A80EB23 from hkp server keys.gnupg.net
gpg: key 4A80EB23: public key "Replicant project release key <contact@replicant.us>" imported
gpg: 3 marginal(s) needed, 1 complete(s) needed, classic trust model
gpg: depth: 0 valid: 2 signed: 63 trust: 0-, 0q, 0n, 0m, 0f, 2u
gpg: depth: 1 valid: 63 signed: 358 trust: 21-, 10q, 6n, 12m, 14f, 0u
gpg: depth: 2 valid: 164 signed: 479 trust: 150-, 2q, 2n, 6m, 4f, 0u
gpg: depth: 3 valid: 4 signed: 16 trust: 4-, 0q, 0n, 0m, 0f, 0u
gpg: next trustdb check due at 2016-10-26
gpg: Total number processed: 1
gpg: imported: 1 (RSA: 1)
```

#5 - 05/28/2018 07:44 PM - Denis 'GNUtoo' Carikli

- Category changed from 171 to Website and wiki content

Files

replicant.pub	4.6 KB	07/16/2016	Tiberiu T
---------------	--------	------------	-----------